

Company name : _____
 Order n° : _____
 Reference : _____
 Delivery address : _____

Delivery time wished

ORDER

QUOTATION

**2 PANELS LANDING DOOR
 CENTRAL OPENING**

ECOSIL 2V OC



Qty : _____ CO : _____ CH : _____

Doors are supplied primer finished, with an aluminium sill, small size toe guard, fixing brackets.

- Standard facade following dwg 209300
 Overhang in shaft : _____ mm → Jam for mechanical locking (*)
 Wall brackets for fixing in shaft (*)
- Small facade following dwg 528500

PUSH BUTTON BOXES AND CUT OUT

- Without any cut out
 Push button box "Call" (*)
 Push button "Call + Present" (*)
 Antivandal push button box "Call" (*)
 Antivandal push button box "Call + Present" (*)
 Without push button box
- Standard cut out : 48 x 70 mm
 Special cut out : W _____ H _____ (*)
 Additionnal cut out : W _____ H _____ at : _____ /floor (*)
 Cut out in the crossbeam : W _____ H _____ centered on : Facade (*)
 Clear opening (*)

FINISHING AND GLAZING

- Grain 220 brushed stainless steel cladding (*) Engraved stainless steel cladding (*)
 On full facade - Nb of doors : _____ On panels only - Nb of doors : _____
- Fireproof glazing (*) On full facade (4 glasses) - Nb of doors : _____
 Non fireproof glazing (*) On panels only (2 glasses) - Nb of doors : _____

SILLS / MISCELLANEOUS

- Standard aluminium sill Non reinforced st. steel sill (*) Reinforced st. steel sill (*) Iron sill (*) Reinforced alu sill (*)
- Cover strips (*) → EZ sheet iron Grain 220 st. Steel Engraved st. Steel
- Stainless steel small size toe guard (*) Safety release contact (*)
- Release key - Qty (*) : _____ Fixing dowels (*) IP 54 waterproof option (*)

**2 PANELS CAR DOOR
 CENTRAL OPENING**

JET-S



Qty : _____ PL : _____ HL : _____

→ Total height from sill to operator brackets : _____ mm (Maximum height under : CH + 300 mm)

- Mechanical locking system (VPC) (*) IP 54 waterproof option (*)
 Electro-magnetic locking to keep doors closed between storages (*)

FINISHING AND GLAZING

- Grain 220 stainless steel cladding (*) Engraved stainless steel cladding (*)
 Glazing (*)

SILLS / MISCELLANEOUS

- Standard aluminium sill Non reinforced st. steel sill (*) Reinforced st. steel sill (*) Iron sill (*) Reinforced alu sill (*)
- Infrared cell curtain with fixing parts (*) Infrared cell with fixing parts (*)
- Large size toe guard (785mm) -EN81- DELTACAP retractable toe guard (*) EZ sheet iron
- Electrogalvanized sheet iron William 2 (pit from 500 to 660 mm) St. steel (*)
- Stainless steel (*) Jack 2 (pit from 660 to 780 mm) Fitting kit (*)
- Averell 2 (pit > 780 mm) Contact kit (*)

MISCELLANEOUS

Add the quotation to the order

(*)With additional price and/or delay