

Company name : \_\_\_\_\_  
 Order n° : \_\_\_\_\_  
 Reference : \_\_\_\_\_  
 Delivery address : \_\_\_\_\_

**Delivery time wished**

**ORDER**

**QUOTATION**

**4 PANELS LANDING DOOR  
 CENTRAL OPENING**

**ECOSIL 4V OM**



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

**Doors are supplied primer finished, with an aluminium sill, small size toe guard, fixing brackets.**

- Standard facade following dwg 216500  
 Overhang in shaft : \_\_\_\_\_ mm →  Jam for mechanical locking (\*)  
 Wall brackets for fixing in shaft (\*)
- Small facade following dwg 528600

**PUSH BUTTON BOXES AND CUT OUT**

- Without any cut out  
 Push button box "Call" (\*)  
 Push button "Call + Present" (\*)  
 Antivandal push button box "Call" (\*)  
 Antivandal push button box "Call + Present" (\*)  
 Without push button box
- Standard cut out : 48 x 70 mm **Maxi depth 30 mm**  
 Special cut out : W \_\_\_\_\_ H \_\_\_\_\_ (\*)  
 Additionnal cut out : W \_\_\_\_\_ H \_\_\_\_\_ at : \_\_\_\_\_ /floor (\*)  
 Cut out in the crossbeam : W \_\_\_\_\_ H \_\_\_\_\_ centered on :  Facade (\*)  
 Clear opening (\*)

**FINISHING AND GLAZING**

- Grain 220 brushed stainless steel cladding (\*)  Engraved stainless steel cladding (\*)  
 On full facade - Nb of doors : \_\_\_\_\_  On panels only - Nb of doors : \_\_\_\_\_
- Non fireproof glazing (\*)  
 On full facade (6 glasses) - Nb of doors : \_\_\_\_\_  
 On panels only (4 glasses) - Nb of doors : \_\_\_\_\_

**SILLS / MISCELLANEOUS**

- Standard aluminium sill  Non reinforced st. steel sill (\*)  Reinforced st. steel sill (\*)  Iron sill (\*)  Reinforced alu sill (\*)  
 Cover strips (\*) →  EZ sheet iron  Grain 220 st. Steel  Engraved st. Steel  
 Stainless steel small size toe guard (\*)  Safety release contact (\*)  
 Release key - Qty (\*) : \_\_\_\_\_  Fixing dowels (\*)  IP 54 waterproof option (\*)

**4 PANELS CAR DOOR  
 CENTRAL OPENING**

**JET-S**



Qty : \_\_\_\_\_ PL : \_\_\_\_\_ HL : \_\_\_\_\_

→ Total height from sill to operator brackets : \_\_\_\_\_ mm (Maximum height under : CH + 300 mm)

- Mechanical locking system (VPC) (\*)  IP 54 waterproof option (\*)  
 Electro-magnetic locking to keep doors closed between storages (\*)

**FINISHING AND GLAZING**

- Grain 220 stainless steel cladding (\*)  Engraved stainless steel cladding (\*)  
 Glazing (\*)

**SILLS / MISCELLANEOUS**

- Standard aluminium sill  Non reinforced st. steel sill (\*)  Reinforced st. steel sill (\*)  Iron sill (\*)  Reinforced alu sill (\*)  
 Infrared cell curtain with fixing parts (\*)  Infrared cell with fixing parts (\*)  
 Large size toe guard (785mm) -EN81-  DELTACAP retractable toe guard (\*)  EZ sheet iron  
 Electrogalvanized sheet iron  William 2 (pit from 500 to 660 mm)  St. steel (\*)  
 Stainless steel (\*)  Jack 2 (pit from 660 to 780 mm)  Fitting kit (\*)  
 Averell 2 (pit > 780 mm)  Contact kit (\*)

**MISCELLANEOUS**

**Add the quotation to the order**

(\*)With additional price and/or delay