

Company name : _____
 Order n° : _____
 Reference : _____
 Delivery address : _____

Delivery time wished

ORDER


QUOTATION

**3 PANELS LANDING DOOR
 SIDE OPENING**

POLYGAM 3V OT




Sliding to the left



Qty : _____ CO _____ CH _____

Sliding to the right



Qty : _____ CO _____ CH _____

Doors are supplied primer finished, with duraluminium sill, small size toe guard, fixing brackets.

Full facade (standard) Small size

Overhang in shaft (maxi 230 mm) : _____ mm → m for mechanical release (*)
 Chaises pour fixation en gaine (*) (PAF ≥ 90)

PUSH BUTTON BOX AND CUT OUT

- Standard push button cut out 48 x 70
- Without push button cut out
- Push button box "Call" (*)
- Push button "Call + Present" (*)
- Without push button cut out
- Level indicator cut out in the crossbeam W _____ x H _____ (*)
- Centered on : Clear opening Facade
- Additionnal cut out : W _____ H _____ at : _____ /floor (*)

STAINLESS STEEL FINISHING

- Grain 220 brushed stainless steel cladding (*)
- On full facade - Nb of doors : _____
- Stainless steel trolleys (*)
- Engraved stainless steel cladding (*)
- On panels only - Nb of doors : _____

MISCELLANEOUS OPTIONS

- Non reinforced st. Steel sill (*)
- Stainless steel toe guard (*)
- Cover strips (*)
- Release key (*)
- Seuil inox renforcé (*)
- EZ sheet iron
- Gr. 220 brushed st. Steel (*)
- IP 54 waterproof electrical equipment (*)
- Iron sill (*)
- Safety release contact (*)
- Engraved stainless steel
- Fixing dowels (*)

**3 PANELS CAR DOOR
 SIDE OPENING**

ROC 3V OT



Sliding to the left - Qty : _____ CO _____ CH _____

Sliding to the right - Qty : _____ CO _____ CH _____

→ Total height from sill to operator brackets : _____ mm (Maximum height under : CH + 300 mm)

- Mechanical locking system (VPC) (*)
- Electro-magnetic locking (*)
- VVVF automatic reinitialization device (*)
- VVVF and electrical components IP54 waterproof (*)

STAINLESS STEEL FINISHING

- Grain 220 brushed stainless steel cladding (*)
- Engraved stainless steel cladding (*)

MISCELLANEOUS OPTIONS

- Reinforced st. steel sill (*)
- Non reinforced st. steel sill (*) (Small clear openings)
- Iron sill (*)
- Infrared cell with fixing parts (*)
- Infrared cells curtain with fixing parts (*)
- Large size toe guard (785mm) -EN81-
- Electrogalvanized sheet iron
- DELTACAP retractable toe guard (*)
- William 2 (pit from 500 to 660 mm)
- Jack 2 (pit from 660 to 780 mm)
- Averell 2 (pit > 780 mm)
- Adaptation kit (*)
- Contact kit (*)
- EZ sheet iron (*)
- Stainless steel (*)

MISCELLANEOUS

Add the quotation to the order

(*)With additional price and/or delay