

Company name : _____
 Order n° : _____
 Reference : _____
 Delivery address : _____

Delivery time wished


ORDER

QUOTATION


**3 PANELS LANDING DOOR
 SIDE OPENING**



Sliding to the left side



Sliding to the right side



Qty : _____ CO : _____ CH : _____ Qté : _____ PL : _____ HL : _____

Doors are supplied primer finished, with aluminium sill, small size toe guard, fixing brackets.

- Full facade / Dwg 2263800
- Small facade acc. Dwg. 2263900
- Separated parts
- Overhang in shaft : _____ mm
- Cam for mechanical locking (*)

PUSH BUTTON BOXES AND CUT OUT

- 48 x 70 standard push button cut out
- Without push button cut out
- Push button box "Call" (*)
- Special cut out : W _____ H _____ (*)
- Push button box "Call + Present" (*)
- Additionnal cut out : W _____ H _____ axis : _____ /ground (*)
- Antivandal push button box "Call" (*)
- Cut out in the crossbeam : W _____ H _____ centered on CO (*)
- Antivandal push button box "Call + Present" (*)
- Maximum depth 60 mm
- Without push button box

FINISHING

- Grain 220 brushed stainless steel(*)
- Engraved stainless steel (*)
- Nb of doors : _____
- Nb of doors : _____

SEUIL OPTIONNEL / DIVERS

- Standard aluminium sill
- NON reinforced stainless steel sill (*)
- Release key - Qty (*) : _____
- Stainless steel small size toe guard (*)
- Fixing dowels (*)

**3 PANELS
 SIDE OPENING**

**LASER
 3VOT**



Sliding to the left - Qty : _____ CO _____ CH _____ Sliding to the right - Qty : _____ CO _____ CH _____

- Total height from sill to operator brackets : _____ mm
- Maxi height under fixings : CH + 220 mm**
- Height under fixings CO > 220 mm <= 270 mm**
- Mechanical locking system (VPC) (*)
- Then Lengthened fasteners (*)
- Electro-magnetic locking (*)

FINISHING

- Grain 220 brushed stainless steel cladding (*)
- Engraved stainless steel cladding (*)

SILLS AND MISCELLANEOUS OPTIONS

- Standard aluminium sill
- NON reinforced stainless steel sill (*)
- Infrared cells curtain with fixing parts (*)
- Infrared cell (*)
- Large size toe guard (785mm) -EN81-
- DELTACAP retractable toe guard (*)
- Electrogalvanized sheet iron
- William 2** (pit from 500 to 660 mm)
- Jack 2** (pit from 660 to 780 mm)
- Averell 2** (pit > 780 mm)
- EZ sheet iron(*)
- Stainless steel(*)
- St. steel (*)
- Adaptation kit(*)
- Contact kit (*)

MISCELLANEOUS

Add the quotation to the order

(*)With additional price and/or delay