

JET-S

2 Panel Side-opening Car door



We've got the perfect door to suit your lift !



Repair



Modernisation

2PSO Car door

Key features

- 




2PSO Car door overall dimensions

Dimensions in mm


Clear opening (PL)	600	650	700	750	800	850	900	950	1000	1100	1200	1300
Clear Height (HL)	1900 to 2500 according clear opening											
Operator overall dimensions	985	1060	1135	1210	1285	1360	1435	1510	1585	1735	1885	2035
Operator height	409 (546 included motor)											
Operator width	154 included motor											
Car door Locking												
Fixing height under console	0 mini - 330 maxi											
Sill width	135 (85 mini in aluminium - 79 mini in stainless steel)											
Light curtain	Fixed											

JET-S CAR DOOR RANGE


Finishes




RAL 9005 Primer



Leather grain
stainless steel



Linen textured
stainless steel



Brushed
stainless steel

Other finishes
Contact us

Benefits

- ✓ Adaptable with or without modification of the car entrance columns
- ✓ Compatible with existing landing doors (SLYCMA or other brands)
- ✓ Integrates advanced technological performance
- ✓ Ensures perfect compatibility between your elevator and the car door
- ✓ Without skate, with movable skate or fixed blade
- ✓ Custom-made sill and panels

Certifications

Certifications	JETS
EN 81-20 / 50	✓
EN 81-71 - Cat1 et Cat2	✓

Environments

Industry

Malls

Hospitals

Offices

Housing

Airports

Social housing

Hotels



Slycma is a signatory of the Code of Good Practice established by the French Lift Federation, to which it has belonged since its creation.

Our quality approach :

Certified ISO 9001 and ISO 14001, Slycma is also regularly audited by its customers.



Contact details

LYON Head Office

235 rue du Général de Gaulle
69530 Brignais
Tél: +33 (0)4 78 86 81 00
slycma@slycma.com


PARIS Branches

34 route de Longjumeau
91380 Chilly Mazarin
Tél. : +33 (0)1 69 79 32 10
magasin.mazarin@slycma.com

16 rue Maurice Thorez
93200 SAINT DENIS
Tél. : +33 (0)1 48 23 91 92

JET-S

2 Panel Central-opening Car door



We've got the perfect door to suit your lift !



Repair



Modernisation

JET-S

Key features

- Panels thickness: 2.0 mm
- Mechanism support : protected sheet metal, 3.0 mm
- Trolleys: protected sheet metal, 3.0 mm
- Upper guide rail : protected solid steel, 40 x 10 mm
- Standard aluminum sill
- Number of starts per hour: > 360 cycles/hour
- Brushless motorization with control via SLYCMA SD 02 VF board
- Asynchronous motorization with control via SLYCMA ARIANE VF board
- Power maintained during travel
- Toothed belt drive




2PCO – Car door overall dimensions

Dimensions in mm


Clear opening (PL)	600	650	700	750	800	850	900	950	1000	1100
Clear Height (HL)	1900 to 2500 according clear opening									
Operator overall dimensions	1270	1370	1470	1570	1670	1770	1870	1970	2070	2270
Operator height	411 (548 included motor)									
Operator width	154 included motor									
Car door Locking										
Fixing height under console	0 mini - 330 maxi									
Sill width	135 (38 mm mini)									
Light curtain	Fixed									

JET-S CAR DOOR RANGE


Finishes




RAL 9005 Primer



Leather grain
stainless steel



Linen textured
stainless steel



Brushed
stainless steel

Other finishes
Contact us

Benefits

- ✓ Adaptable with or without modification of the car entrance columns
- ✓ Compatible with existing landing doors (SLYCMA or other brands)
- ✓ Integrates advanced technological performance
- ✓ Ensures perfect compatibility between your elevator and the car door
- ✓ Without skate, with movable skate or fixed blade
- ✓ Custom-made sill and panels

Certifications

Certifications	JETS
EN 81-20 / 50	✓
EN 81-71 - Cat1 et Cat2	✓

Environments

Industry

Malls

Hospitals

Offices

Housing

Airports

Social housing

Hotels



Slycma is a signatory of the Code of Good Practice established by the French Lift Federation, to which it has belonged since its creation.

Our quality approach :

Certified ISO 9001 and ISO 14001, Slycma is also regularly audited by its customers.



Contact details

LYON Head Office

235 rue du Général de Gaulle
69530 Brignais
Tél: +33 (0)4 78 86 81 00
slycma@slycma.com

PARIS Branches

34 route de Longjumeau
91380 Chilly Mazarin
Tél. : +33 (0)1 69 79 32 10
magasin.mazarin@slycma.com

16 rue Maurice Thorez
93200 SAINT DENIS
Tél. : +33 (0)1 48 23 91 92

JET-S

4 Panel Central-Opening Car Door



We've got the perfect door to suit your lift !



Repair



Modernisation

JET-S

4PCO Car Door

Key features

- Panels thickness: 2.0 mm
- Mechanism support : protected sheet metal, 3.0 mm
- Trolleys: protected sheet metal, 3.0 mm
- Upper guide rail : protected solid steel, 40 x 10 mm
- Standard aluminum sill
- Number of starts per hour: > 360 cycles/hour
- Brushless motorization with control via SLYCMA SD 02 VF board
- Asynchronous motorization with control via SLYCMA ARIANE VF board
- Power maintained during travel
- Toothed belt drive




4PCO – Car door overall dimensions

Dimensions in mm


Clear opening (PL)	1200	1300	1400	1500	1600	1700	1800	2000	2100	2200
Clear Height (HL)	1900 to 2500 according clear opening									
Operator overall dimensions	1904	2054	2204	2354	2504	2654	2804	3104	3254	3404
Operator height	397 (576 including motor in top position)									
Operator width	291 included motor									
Car door Locking										
Fixing height under console	30 mini - 312 maxi									
Sill width	135 (38 mm mini)									
Light curtain	Fixed									

JET-S CAR DOOR RANGE


Finishes




RAL 9005 Primer



Leather grain
stainless steel



Linen textured
stainless steel



Brushed
stainless steel

Other finishes
Contact us

Benefits

- ✓ Adaptable with or without modification of the car entrance columns
- ✓ Compatible with existing landing doors (SLYCMA or other brands)
- ✓ Integrates advanced technological performance
- ✓ Ensures perfect compatibility between your elevator and the car door
- ✓ Without skate, with movable skate or fixed blade
- ✓ Custom-made sill and panels

Certifications

Certifications	JETS
EN 81-20 / 50	✓
EN 81-71 - Cat1 et Cat2	✓

Environments

Industry

Malls

Hospitals

Offices

Housing

Airports

Social housing

Hotels



Slycma is a signatory of the Code of Good Practice established by the French Lift Federation, to which it has belonged since its creation.

Our quality approach :

Certified ISO 9001 and ISO 14001, Slycma is also regularly audited by its customers.



Contact details

LYON Head Office

235 rue du Général de Gaulle
69530 Brignais
Tél: +33 (0)4 78 86 81 00
slycma@slycma.com

PARIS Branches

34 route de Longjumeau
91380 Chilly Mazarin
Tél. : +33 (0)1 69 79 32 10
magasin.mazarin@slycma.com

16 rue Maurice Thorez
93200 SAINT DENIS
Tél. : +33 (0)1 48 23 91 92