

# PAC

81S Landing door & 85S Car door



SLYCMA Creation 2023 - Photos by Fabrice Ferrer - SLYCMA - Photos and Illustrations are non-contractual. Subject to change. Reproduction, even partial, is prohibited.



We've got the perfect door to suit your lift !



Creation



Modernisation

# PAC 81 S & 85 S

## Landing doors and Car doors

### Key features

- Landing door available in 3 versions : manual, automatic, and simultaneous drive
- Jams steel thickness : 3 mm - Panels steel sheet thickness : 1.5 mm
- Reinforced, protected top guide rail
- Heavy-duty aluminium sill with large section or steel sill
- Counter rollers  $\varnothing$  60 mm with steel bearings
- Genalock lock
- S-curve available on request for car door
- Frequency inverter control with position control (Automatic option)



Frequency inverter control cabinet – 400 W


### Landing doors and car doors dimensions

Dimensions in mm

|                                     | MINI   | MAXI | MAXI       |
|-------------------------------------|--------|------|------------|
| Manual - fire-resistant             | 700    | 2600 | Up to 3000 |
| Simultaneous drive - fire-resistant | 700    | 2600 | Up to 3000 |
| Automatic - non fire-resistant      | 700    | 3000 | Up to 3000 |
| Lintel height                       | 185 mm |      |            |

# THE PAC RANGE

## Standard finishes



Standard primer  
RAL 9005



Solid stainless  
steel



Other finish  
Please contact us

## Benefits

- ✓ High level of resistance for all applications
- ✓ Designed for areas requiring maximum clear opening within minimal space requirements
- ✓ Available in manual, automatic, or simultaneous drive versions
- ✓ Compatible with PAC 85 car door
- ✓ Quiet and robust operation

## Certifications

| Certifications | Manual landing door | Automatic landing door | Simultaneous drive landing door |
|----------------|---------------------|------------------------|---------------------------------|
| EN 81-58       | E120 - EW 60        | -                      | E120 - EW 60                    |
| EN 81-20 / 50  | Compliant           | Compliant              | Compliant                       |
| EN 81-21       | Compliant           | Compliant              | Compliant                       |
| EN 81-70       | Compliant           | Compliant              | Compliant                       |
| EN 81-71       | -                   | -                      | -                               |
| 2014/33/UE     | Compliant           | Compliant              | Compliant                       |

## Environments

Industry

Shopping centres

Car lift



Slycma is a signatory of the Code of Good Practice established by the French Lift Federation, to which it has belonged since its creation.

### Our quality approach :

Certified ISO 9001 and ISO 14001, Slycma is also regularly audited by its customers.



### Contact details

#### LYON Head Office

235 rue du Général de Gaulle  
69530 Brignais  
Tél: +33 (0)4 78 86 81 00  
slycma@slycma.com

#### PARIS Branches

34 route de Longjumeau  
91380 Chilly Mazarin  
Tél. : +33 (0)1 69 79 32 10  
magasin.mazarin@slycma.com

---

16 rue Maurice Thorez  
93200 SAINT DENIS  
Tél. : +33 (0)1 48 23 91 92