

Company :
 Order n° :
 Lift n° :
 Reference :
 Technical contact :
 Delivery address :

Delivery time requested

ORDER

QUOTATION

1 PANEL SWINGING DOOR

EN 81-20

Lynea - GRIII

CO 600 to 1300

Hung on left



Qty : _____

CO : _____

Hung on right



Qty : _____

CH 1200
 Other CH _____ (*)

Frame

- Standard header std 145 mm
- Special header (*) _____ (mini 50) (*)
- Standard uprights 150 mm
- Others : (*) Lock side _____ (mini 90)
Hinges side _____ (mini 70) (maxi 200)
- Stiffeners:**
- End of the opening damper on door closer arm(*)
- Reinforced frame (*)
- Standard SLYCMA push button box(*)
- Call Presence light Send
- Standard cutout 48 x 70 mm
- Without cutout
- Special BB cutout : w _____ x H _____ (*) ^{ES} E120 case yes no
- Indicator cutout /header : w _____ x H _____ (*) non E120
- Corner bead sill Iron sill Toe guard (*) Uprights with lateral holes Uprights without lateral holes

Standard door finishing : primer

- Aesthetic stainless steel (*)**
 frame and panel on landing side
 panel on shaft side
 Brushed Polished 220 . 304L stainless steel
 Brushed Polished 220 . 316L stainless steel
 Engraved leather D42. 304L stainless steel
 Linen 304L stainless steel
- Massive stainless steel (*)**
 304L rough rolled stainless steel
 316L rough rolled stainless steel
- Powder painting (*)** RAL color: _____
- Other finishings : Contact us**

Accessories finishing

- tWhole aluminium anodized natural tone (std)
- Other : _____ (*) (contact us)

Standard lock Genalock range

- GENALOCK lock** **Unlocking :** parallel perpendicular
- KRONENBERG lock (*)** **Unlocking :** parallel perpendicular IP54 (*) available only with Kronenberg and header > 85mm
- LR180E Electrical PRUDHOMME lock (*)** 24 Vcc (*) 48 Vcc (*)
- EN 81-21 safety contacts (Bistable and hinges contact) (*) 24 V 230 V
- on every floors
- only on the door of the lowest floor
- Adapted release height (*)** ^{ES} Specify cam working direction and unbolting roller height following drawing 24273 _____
- parallel to the wall (pushing) parallel to the cabine (pulling) perpendicular
- Unbolting on hinges side (*)** ^{ES} Specify cam working direction and unbolting roller height : _____

Other options

- Stop at 90° (*)
- Unlocking key (*)
- Fixing kit (*) (6 squares + dowels)

Literature French English German Italian

Miscellaneous