Slycma
EXPERT FOR LEFT DOOR

: +33 (0)4.78.86.81.00
: +33 (0)4.78.86.81.08
: slycma@slycma.com
: www.slycma.com

Company : .....
Order n° : .....
Lift n° : .....
Reference : .....
Technical contact : .....
Delivery address : .....

Delivery time requested

☐ ORDER ☐ QUOTATION

ARTICULATED SLIDING CAR DOOR

EN 81-20

Pac 85

CO 700 to 3000

Sliding to the left side seen from landing

Qty : _____ CO : _____ x CH : _____

Sliding to the right side seen from landing

Qty : _____ CO : _____ x CH : _____

☐ **MANUAL**
A mini = 270 mm

☐ **AUTOMATIC** motorization with VVVF (*)
A mini = 270 mm

A Dimension: _____
(A < 270 - Contact us)

☐ **SIMULTANEOUS DRIVING** with PAC 81(*)
A mini = 270 mm

Gap between sill (simultaneous execution)
☐ 30 mm (standard)
☐ 25 mm (*)
☐ 20 mm (*)

Finishing - Standard primer finish - RAL 9005

☐ **Massive stainless steel** (*)

☐ 304L rough rolled stainless steel
☐ 316 L rough rolled stainless steel
☐ Only frame components in st. steel
☐ Full massive stainless steel
☐ Top and bottom tracks in stainless steel (except guiding rail) (*)
☐ Top guiding rail 35 x 10 in stainless steel

Options

Sill :	☐ Iron (*)	☐ 304L st. steel (*)	☐ 316L st. stee l(*)
Toe guard (*)	☐ Galvanised iron	☐ 304L st. steel (*)	☐ 316L st. steel (*)
Curve in "S" (*)	☐		

☐ Additionnal detection cell (*) - Quantity :_____
☐ IP54 Waterproof (*) (manual - other : contact us)

Device for blocking between floors for manual doors

☐ Without (Not EN 81-20)

☐ Electromagnetic locking EN 81-20 (*)
to keep the doors closed between floors

NOTA : Blocking with the clutch on automatic doors

• Literature ☐ French ☐ English ☐ German ☐ Italian

Miscellaneous

September 2017

Attach the quotation to the order

(*) with extra cost and / or delivery time