

Company :
 Order n° :
 Lift n° :
 Reference :
 Technical contact :
 Delivery address :

Delivery time requested

ORDER

QUOTATION

ARTICULATED SLIDING CAR DOOR

EN 81-20

Pac 85

CO 700 to 3000

Sliding to the left side seen from landing



Qty : _____ CO : _____ x CH : _____

Sliding to the right side seen from landing



Qty : _____ CO : _____ x CH : _____

MANUAL
A mini = 270 mm

AUTOMATIC motorization with VVVF (*)
A mini = 270 mm

SIMULTANEOUS DRIVING with PAC 81(*)
A mini = 270 mm

A Dimension: _____
(A < 270 - Contact us)

Gap between sills 30 mm (standard)
 (simultaneous execution) 25 mm (*)
 20 mm (*)

Finishing - Standard primer finish - RAL 9005

Massive stainless steel (*)

- 304L rough rolled stainless steel 316 L rough rolled stainless steel
 Only frame components in st. steel Full massive stainless steel
 Top and bottom tracks in stainless steel (except guiding rail) (*)
 Top guiding rail 35 x 10 in stainless steel

Options

- Sill : Iron (*) 304L st. steel (*) 316L st. steel (*)
 Toe guard (*) Galvanised iron 304L st. steel (*) 316L st. steel (*)
 Curve in "S" (*)

Additional detection cell (*) - Quantity : _____

IP54 Waterproof (*) (manual - other : contact us)

Device for blocking between floors for manual doors

- Without (Not EN 81-20) Electromagnetic locking EN 81-20 (*)
 to keep the doors closed between floors

NOTA : Blocking with the clutch on automatic doors

- Literature French English German Italian

Miscellaneous

