Company:			<b>☎</b> : + 33 (0)4.78.86.81.00 <b>æ</b> : + 33 (0)4.78.86.81.08 <b>∞</b> : slycma@slycma.com <b>æ</b> : www.slycma.com
Lift n°:			Delivery time requested
	□ ORDER	□ QUOTATION	
2 PANELS CENTR	AL OPENING	EN 81-20	Gaia 2V OC
CAR DOOR			CO 600 to 1300
			According drawing 2794500
□ Automatic landing door unlocking □ Gaia 2V OL	Qty : CO :	CH :	
r Fixing height under fastening br Maxi 250 mm	ackets : mm		
Other heigt > :  Fixing kit on car roof (*)  2 C-Shaped section + screws ar  standard SLYCMA (Car door CO - according to car width :  Vandal-resistant options (*)			
Category 2 with anti-gripping and fast and Vandal-resistant unlocking device	slow panel's boxing on the whole heigh	t (Cowling of the lock contact included)	
Blocking between floors  ☐ Without (Non EN 81-20)		☐ Car door mechanical locking EN 81-20 - Article 5.2.5.3.1	device between floors (*) :
Stainless steel finishing and gla  304L Polished 220 brushed stainless steel of  304L D42 leather texture st. steel cladding  304L linen stainless steel cladding	sladding $\Box$ Glazing	nt option not available on glazed execution	
Sills  Standard aluminium sill Iron sill (*)	☐ Non reinforced 304 L brushed s ☐ 304 L Reinforced stainless steel	tainless steel sill with removing dust slo sill (*)	ts (*)
Toe guards (*)  Large size toe guard (785mm)  Galvanized iron  304L stainless steel  Sans fourniture de la tôle garde pieds  Options (*)	☐ DELTACAP retractable toe guard ☐ William (pit from 500 to 660 ☐ Jack 2 (pit from 660 to 780 ☐ Galvanized iron	) mm) $\Box$	Adaptation kit Contact cam kit
□ Infrared cells curtain with fixing kit			
Literature ☐ French ☐ f	nglish □ German	□Italian	
Miscellaneous			