

Company :
 Order n° :
 Lift n° :
 Reference :
 Technical contact :
 Delivery address :

Delivery time requested

ORDER

QUOTATION

2 PANELS SIDE OPENING CAR DOOR

EN 81-20

Gaia 2V OL

CO 600 to 1300

Sliding to the left side according drawing 2794400

Sliding to the right side according drawing 2794400



Qty : _____ CO : _____ CH : _____

Qty : _____ CO : _____ CH : _____

- Automatic landing door unlocking
 - Gaia 2V OL

☛ Fixing height under fastening brackets : _____ mm
 Maxi 250 mm

Other height > : _____ (*) - Contact us for feasibility

- Fixing kit on car roof (*)
 - 2 C-Shaped section + screws and bolts
 - standard SLYCMA (Car door CO + 150 mm)
 - according to car width : _____

Vandal-resistant options (*)

- Category 2 with anti-gripping and fast and slow panel's boxing on the whole height (Cowling of the lock contact included)
- Vandal-resistant unlocking device

Blocking between floors

- Without (Non EN 81-20)
- Car door mechanical locking device between floors (*) :
 EN 81-20 - Article 5.2.5.3.1

Stainless steel finishing and glazing (*)

- 304L Polished 220 brushed stainless steel cladding
- 304L D42 leather texture st. steel cladding
- 304L linen stainless steel cladding
- Glazing
 - Vandal-resistant option not available on glazed execution

Sills

- Standard aluminium sill
- Iron sill (*)
- Non reinforced 304 L brushed stainless steel sill with removing dust slots (*)
- 304 L Reinforced stainless steel sill (*)

Toe guards (*)

- Large size toe guard (785mm)
 - Galvanized iron
 - 304L stainless steel
- Sans fourniture de la tôle garde pieds
- DELTACAP retractable toe guard
 - William (pit from 500 to 660 mm)
 - Jack 2 (pit from 660 to 780 mm)
 - Galvanized iron
 - 304L stainless steel
- Adaptation kit
- Contact cam kit

Options (*)

- Infrared cells curtain with fixing kit

- Literature French English German Italian

Miscellaneous

Attach the quotation with the order

(*) with extra cost and/or delivery time