

Company : .....  
 Order n° : .....  
 Lift n° : .....  
 Reference : .....  
 Technical contact : .....  
 Delivery address : .....

Delivery time requested

☐ ORDER

☐ QUOTATION

## 2 PANELS SIDE OPENING CAR DOOR

EN 81 - 20

**Jet-S 2V OL**

CO 600 to 1300

Qté : \_\_\_\_\_ PL : \_\_\_\_\_ HL : \_\_\_\_\_

Qté : \_\_\_\_\_ PL : \_\_\_\_\_ HL : \_\_\_\_\_

☐ Landing door unlocking :

Type : \_\_\_\_\_ Brand : \_\_\_\_\_

Model : \_\_\_\_\_ RC : \_\_\_\_\_

☐ left ☐ right

☐ Swinging door - Hung side seen from landing : :

☞ Fixing height under fastening brackets : \_\_\_\_\_ mm

• Car entrance columns

☐ Modified / replaced by customer

☐ Retained (supplying of special panels and sill to fit the existing car entrance columns according to sketch CRQC1)

• Fixing kit on car roof (\*)

☐ 2 C-Shaped section + screws and bolts

☐ standard SLYCMA (Car door CO + 150 mm)

☐ For P8 car

☐ according to car width : \_\_\_\_\_

☐ 2 Fixing stiffening adjustable brackets CO >= 1100

☐ 1 Additionnal fixing stiffening adjustable bracket and 1 backup support leg (\*)

### Vandal-resistant options (\*)

☐ **Level 1** with fast panel's boxing on the whole height

☐ Fast panel anti-gripping

☐ **Level 2** with anti-gripping and panel's boxing on the panels' whole height

### Blocking between floors

☐ Without (Non EN 81-20)

☐ EN 81-20 blocker (\*)

☐ Mechanical car door locking device (VPC) (\*) :

EN 81-20 - Article 5.2.5.3.1

Nb of cams for landing doors (1 per floor) : \_\_\_\_\_

### Stainless steel finishing and glazing (\*)

☐ 304L Polished 220 brushed stainless steel cladding

☐ 304L D42 leather texture st. steel cladding

☐ 304L linen stainless steel cladding

☐ Glazing (with GAIA landing door fireproof glazing)

☐ Glazing (with GAIA landing door non fireproof glazing)

### Sills

☐ Standard aluminium sill

☐ Iron sill (\*)

☐ Non reinforced 304 L brushed stainless steel sill with removing dust slots (\*) } Existing sill width : \_\_\_\_\_

☐ 304 L Reinforced stainless steel sill (\*)

### Toe guards (\*)

☐ Large size toe guard (785mm)

☐ Galvanized iron

☐ Stainless steel

☐ DELTACAP retractable toe guard

☐ William (pit from 500 to 660 mm)

☐ Jack 2 (pit from 660 to 780 mm)

☐ Galvanized iron ☐ Stainless steel

☐ Adaptation kit

☐ Contact cam kit

☐ Black

### Options (\*)

☐ IP 54 contacts

☐ Infrared cells curtain with fixing kit

☐ Infrared cell with fixing kit

☐ Swinging door unlocking cam and sill notching for lock lever pathway

• Literature

☐ French

☐ English

☐ German

☐ Italian

### Miscellaneous