Company:			≅ : + 33 (0)4.78.86.81.00 √ : + 33 (0)4.78.86.81.08 ∨ : slycma@slycma.com ♦ : www.slycma.com
Lift n° :			Delivery time requested
	□ ORDER	□ QUOTATION	\
2 PANELS CENTR CAR DOOR	RAL OPENING	EN 81-20	Rhea 2V OC CO 600 to 1100
		-	Following drawing 2690100
☐ Automatic landing door unlocking ☐ Rhea 2V OC	Qty : C0 :	CH:	
G		☐ Right	
 Fixing kit on car roof (*) □ 2 C-Shaped section + screws and bolts □ standard SLYCMA (Car door CO + 150) □ according to car width : 	()- outda	et us to control leasibility	
Vandal-resistant option (*)			
Level 1 with fast panel's boxing on the whole h	eight	Fast panels' anti-gripping	
Blocking between floors Without (Non EN 81-20)	☐ EN 81-20 blocker (*) ☐ Mechanical car door locking device (VPC) (*): EN 81-20 - Article 5.2.5.3.1 Nb of cams for landing doors (1 per floor):		
Stainless steel finishing and gl	azing (*)		() · · · /
□ 304L Polished 220 brushed stainless steel □ 304L D42 leather texture st. steel □ 304L linen stainless steel	☐ Glazing - following drawing 2697 - Vandal-resistant option not available of ☐ Panoramic (panels edges and ☐ Panoramic other finishes for p ☐ Anodizing ☐ Brighten ☐ Full Glass	n glazed executions sill aluminium anodized natural shape) vanels edges and sill	(following SLYCMA reference)
Sills	i un diass		
☐ Standard aluminium sill☐ Non reinforced 304 L brushed stainless steel si	ll with removing dust slots (*)		
Toe guard (*)	DELTACAD verbus etable too avverd		
☐ Large size toe guard (785mm) ☐ Galvanised iron ☐ 304 L stainless steel ☐ Without toe guard	☐ DELTACAP retractable toe guard ☐ William (pit from 500 to 660 ☐ Jack 2 (pit from 660 to 780 ☐ Galvanised iron ☐ :		☐ Adaptation kit ☐ Contact kit
Options (*)			
☐ Infrared cells curtain with fixing kit ☐ Swinging door unlocking cam on panel . Unlocking roller height : mm			
• Literature	English German	□Italian	
Miscellaneous			