

Company :
 Order n° :
 Lift n° :
 Reference :
 Technical contact :
 Delivery address :

Delivery time requested

ORDER

QUOTATION

2 PANELS SIDE OPENING CAR DOOR

EN 81-20

Rhea 2V OL

CO 600 to 1300

Left sliding following drawing 2689600

Right sliding following drawing 2689600



Qty : _____ CO : _____ CH : _____

Qty : _____ CO : _____ CH : _____

- Automatic landing door unlocking
 Rhea 2V OL

- Swinging door - Hung side seen from landing : left right

☛ Fixing height under fastening brackets : _____ mm
 Sheet-metal : Maxi 280 mm
 Glazed : Maxi 335 mm
 Other height > : _____ (*) - Contact us to control feasibility

- Fixing kit on car roof (*)
 - 2 C-Shaped section + screws and bolts
 - standard SLYCMA (Car door CO + 150)
 - according to car width : _____

Vandal-resistant options (*)

- Level 1 with fast panel's boxing on the whole height Fast panels' anti-gripping
 Slow panels' boxing

Blocking between floors

- Without (Non EN 81-20) EN 81-20 blocker (*) Mechanical car door locking device (VPC) (*) :
 EN 81-20 - Article 5.2.5.3.1
 Nb of cams for landing doors (1 per floor) : _____

Stainless steel finishing and glazing (*)

- 304L Polished 220 brushed stainless steel Glazing - following drawing 2697200 - *Caution Maxi CO glazed = 1100* - Others contact us
 304L D42 leather texture st. steel - Vandal-resistant option non available on glazed executions
 304L linen stainless steel Panoramic (panels edges and sill aluminium anodized natural shape)
 Panoramic other finishes for panels edges and sill
 Anodizing Brightening Shape : _____ (following SLYCMA reference)
 Full Glass

Sills

- Standard aluminium sill Non reinforced 304 L brushed stainless steel sill with removing dust slots (*)
 Iron sill - Sheet metal execution only (*) Reinforced stainless steel sill - Sheet metal execution only (*)

Toe guards (*)

- Large size toe guard (785mm) DELTACAP retractable toe guard
 Galvanised iron William (pit from 500 to 660 mm) Adaptation kit
 304 L stainless steel Jack 2 (pit from 660 to 780 mm) Contact kit
 Without toe guard Galvanised iron Stainless steel

Options (*)

- Infrared cells curtain with fixing kit
 Swinging door unlocking cam on panel
 . Unlocking roller height : _____ mm
- Literature French English German Italian

Divers