

Company : .....  
 Order n° : .....  
 Lift n° : .....  
 Reference : .....  
 Technical contact : .....  
 Delivery address : .....

Delivery time requested

ORDER

QUOTATION

## 2 PANELS SIDE OPENING GLAZED CAR DOOR

EN 81 - 20

Rhea 2PSO

CO 600 to 1300

Left sliding following drawing 2788300



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

Right sliding following drawing 2788300



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

- Automatic landing door unlocking  
 Rhea 2PSO

- Swinging door - Hung side seen from landing :

- left       right

- Swinging door unlocking cam on panel.

*Note that the direction of opening of the car door must be opposite to the hanging side of the swing door*

Unlocking roller height : \_\_\_\_\_ mm

- ☞ Fixing height under fastening brackets : \_\_\_\_\_ mm (mini 35 mm - maxi 300 mm)  
 Other height > : \_\_\_\_\_ (\*) - Contact us to control feasibility

- Fixing kit on car roof (\*)

- 2 C-Shaped section + screws and bolts  
 standard SLYCMA (Car door CO + 150)  
 according to car width : \_\_\_\_\_  
 Additional fixing stiffening adjustable bracket for CO < 1000

### Blocking between floors

- Mechanical car door locking device (VPC)  
 EN 81-20 - Article 5.2.5.3.1 (included in the standard production model)
- EN 81-20 blocker (\*)  
 (with swing door)
- Without (Non EN 81-20)

### Stainless steel finishes (\*)

- 304 Brushed massive stainless steel      ☞ Nb of doors : \_\_\_\_\_  
 RAL powder coating \_\_\_\_\_      ☞ Nb of doors : \_\_\_\_\_
- 304 leather texture massive stainless steel      ☞ Nb of doors : \_\_\_\_\_  
 304 linen massive stainless steel      ☞ Nb of doors : \_\_\_\_\_
- Glazing of the panels
- Panoramic (standard model) : Panels' edge and sill : natural anodised aluminium  
 Panels' edge and sill anodization (\*) - colour : \_\_\_\_\_ (Anodization according to Slycma referential)  
 Full Glass (\*)

### Sills

- Standard aluminium sill       Non reinforced 304 brushed stainless steel sill (\*)

### Toe guards (\*)

- Large size toe guard (785mm)  
 Galvanised iron       DELTACAP retractable toe guard  
 304 L stainless steel       William (pit from 500 to 660 mm)       Adaptation kit  
 Without toe guard       Jack 2 (pit from 660 to 780 mm)       Contact kit  
 Galvanised iron       Stainless steel

### Options (\*)

- Infrared cells curtain with fixing kit  
 Kit for unlocking the lowest landing door from the bottom of pit (EN 81-20) (\*)

- Literature       French       English       German       Italian

### Miscellaneous

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_