

Company : .....  
 Order n° : .....  
 Lift n° : .....  
 Reference : .....  
 Technical contact : .....  
 Delivery address : .....

Delivery time requested

ORDER

QUOTATION

# 3 PANELS SIDE OPENING CAR DOOR

EN 81-20

# Rhea 3V OL

CO 600 to 1100

Left sliding following drawing 2690900



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

Right sliding following drawing 2690900



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

- Landing door unlocking :
  - RHEA 3V
  - Swinging door - Hung side seen from landing :  left  right
  - Other (Contact us) : \_\_\_\_\_
- Fixing height under fastening brackets : \_\_\_\_\_ mm
  - Sheet-metal : Maxi 280 mm
  - Glazed : Maxi 335 mm
  - Others >: \_\_\_\_\_ (\*) - Contact us to control feasibility

- Fixing kit on car roof (\*)
  - 2 C-Shaped section + screws and bolts
  - standard SLYCMA (Car door CO + 150)
  - according to car width : \_\_\_\_\_

## Vandal-resistant options (\*)

- Level 1 with fast panel's boxing on the whole height
- Fast panel anti-gripping
- Intermediary and slow panels' boxing

## Blocking between floors

- Without (Non EN 81-20)
- EN 81-20 blocker (\*)
- Mechanical car door locking device (VPC) (\*) :  
 EN 81-20 - Article 5.2.5.3.1  
 Nb of cams for landing doors (1 per floor) : \_\_\_\_\_

## Stainless steel finishing and glazing (\*)

- 304L Polished 220 brushed stainless steel
- 304L D42 leather texture st. steel
- 304L linen stainless steel
- Glazing - following drawing 2697400  
 - Vandal-resistant option not available on glazed executions
  - Panoramic (panels edges and sill aluminium anodized natural shape)
  - Panoramic other finishes for panels edges and sill
  - Anodizing  Brightening
  - Shape : \_\_\_\_\_ (following SLYCMA reference)
- Full Glass

## Sills

- Standard aluminium sill
- Non reinforced 304 L brushed stainless steel sill with removing dust slots (\*)

## Toe guard (\*)

- Large size toe guard (785mm)
  - Galvanised iron
  - 304 L stainless steel
- Without toe guard
- DELTACAP retractable toe guard
  - William (pit from 500 to 660 mm)
  - Jack 2 (pit from 660 to 780 mm)
  - Galvanised iron  Stainless steel
- Adaptation kit
- Contact kit

## Options (\*)

- Infrared cells curtain with fixing kit
- Swinging door unlocking cam on panel  
 . Unlocking roller height : \_\_\_\_\_ mm

- Literature  French  English  German  Italian

## Miscellaneous