Company : ....
Order n° : ....
Lift n° : ....
Reference : ....
Technical contact : ....
Delivery address : ....

Delivery time requested

☐ ORDER   ☐ QUOTATION

4 PANELS CENTRAL OPENING CAR DOOR   EN 81-20   Rhea 4V OC
CO 600 to 1100

According to drawing 2690300

Qty : _____ CO : _____ CH : _____

- Landing door unlocking :   ☐ RHEA 4V
                                  ☐ Swinging door - Hung side seen from landing :   ☐ left   ☐ right
                                  ☐ Other (Contact us) : _____
☞ Fixing height under fastening brackets : _____ mm
                                  Sheet-metal : Maxi 260 mm
                                  Glazed : Maxi 315 mm
                                  Others >: _____ (*) - Contact us to control feasibility

- Fixing kit on car roof (*)
   ☐ 2 C-Shaped section + screws and bolts
   ☐ standard SLYCMA (Car door CO + 150)
   ☐ according to car width : _____

Vandal-resistant options (*)

☐ Level 1 with fast panel's boxing on the whole height   ☐ Fast panel anti-gripping
                                                              ☐ Intermediary and slow panels' boxing

Blocking between floors

☐ Without (Non EN 81-20)   ☐ EN 81-20 blocker (*)   ☐ Mechanical car door locking device (VPC) (*) :
                                                              EN 81-20 - Article 5.2.5.3.1
                                                              Nb of cams for landing doors (1 per floor) : _____

Finition inox et vitrages (*)

  304L Polished 220 brushed stainless steel   ☐ Glazing - following drawing 2697000
☐ 304L D42 leather texture st. steel   - **Vandal-resistant option not available on glazed executions**
☐ 304L linen stainless steel   ☐ Panoramic (panels edges and sill aluminium anodized natural shape)
                                                   ☐ Panoramic other finishes for panels edges and sill
                                                   ☐ Anodizing   ☐ Brightening   Shape : _____ *(following SLYCMA reference)*
                                                   ☐ Full Glass

Sills

☐ Standard aluminium sill
☐ Non reinforced 304 L brushed stainless steel sill with removing dust slots (*)

Toe guard (*)

☐ Large size toe guard (785mm)   ☐ DELTACAP retractable toe guard
   ☐ Galvanised iron   ☐ William (pit from 500 to 660 mm)   ☐ Adaptation kit
   ☐ 304 L stainless steel   ☐ Jack 2 (pit from 660 to 780 mm)   ☐ Contact kit
☐ Sans tôle garde pieds   ☐ Galvanised iron   ☐ Stainless steel

Options (*)

☐ Infrared cells curtain with fixing kit
☐ Swinging door unlocking cam on panel
   . Unlocking roller height : _____ mm

- Literature   ☐ French   ☐ English   ☐ German   ☐ Italian

Miscellaneous

_____
_____
_____
_____

September 2017

Attach the quotation to the order   (*) with extra cost and /or delivery time