

Company :
 Order n° :
 Lift n° :
 Reference :
 Technical contact :
 Delivery address :

Delivery time requested

ORDER

QUOTATION

2 PANELS SIDE OPENING LANDING DOOR

EN 81 - 20
 EN 81-58
 E 120 - EI 60

GAIA 2 VOL

CO 600 to 1300

Sliding to the left side



Qty : _____ CO : _____ CH : _____

Sliding to the right side



Qty : _____ CO : _____ CH : _____

Small facade (HR) according drawing 2632200

Full facade (FC) according drawing 2630200 (*)

Overhang in shaft : _____ mm

Car door locking required if overhang in shaft > 115mm

E120 door with maximum overhang in shaft maxi 135mm

Cam for mechanical locking (*) Nb of cams : _____ (1 per floor)

Supports for shaft fixing in protected steel (*)

Supports for shaft fixing in 304 L stainless steel (*)

Vandal-resistant options (*)

Level 2 with anti-gripping and whole height fast and slow panels' boxing (Lock contact cowling included)

Vandal-resistant unlocking system

Button boxes and cutouts

"CALL" button box (*)

"CALL" round button(*)

"CALL" Antivandal button box (*)

Without button box

Without cutout

48 x 70 mm button box cutout

Special button box cutout : l _____ x H _____ (*)

Indicator cutout on upright : l _____ x H _____ (*)

axled at : _____ - With fireproof box (*)

Additionnal upright cutout : l _____ x H _____ (*)

axled at : _____ With fireproof box

Header indicator cutout - Maxi depth = 50 mm : l _____ x H _____ (*) - Centered on CO

Finishes (*) (primer finished standard)

304L brushed 220 massive stainless steel

☞ Nb of doors : _____

304L leather texture D42 massive stainless steel ☞ Nb of doors : _____

RAL powder coating _____

☞ Nb of doors : _____

304L linen massive stainless steel

☞ Nb of doors : _____

Other finishes : Contact us

Fireproof glazing (*)

On whole facade (3 glass) - Number of doors : _____

Non fireproof glazing (*)

On panels only (2 glass) - Number of doors : _____

Options

Standard aluminium sill

304 L non reinforced sill (*)

304 L reinforced sill (*)

Iron sill (*)

Stainless steel toe guard (*)

Cover plates (*) ☞ steel to paint

304L brushed st. steel

304L leather texture D42 st. steel

304L linen st. steel

Fixing dowels (*) ☞ protected steel

304L stainless steel

Unlocking key - Qty (*) : _____

EN 81-21 safety contacts (*)

1NO/1NF

2NF

24 V

230 V

☞ On whole floors

On the lowest level door

Contacts cowling (*)

Kit for unlocking the lowest landing door from the botton of pit (EN 81-20) (*)

• Literature

French

English

German

Italian

Miscellaneous
