

Company : .....  
 Order n° : .....  
 Lift n° : .....  
 Reference : .....  
 Technical contact : .....  
 Delivery address : .....

Delivery time requested

ORDER

QUOTATION

## 3 PANELS SIDE OPENING LANDING DOOR

EN 81 - 20  
 EN 81-58  
 E 120 - EI 60

## Gaia 3V OL

CO 700 to 1800

Sliding to the left side



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

Sliding to the right side



Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

**Small facade (HR)** according drawing 2631600

**Full facade (FC)** according drawing 2630000

Overhang in shaft : \_\_\_\_\_ mm

Car door locking required if overhang in shaft > 115mm

E120 door with maximum overhang in shaft maxi 135mm

Cam for mechanical locking (\*)      Nb of cams : \_\_\_\_\_ (1 per floor)

Supports for shaft fixing in protected steel (\*)

Supports for shaft fixing in 304 L stainless steel (\*)

### Vandal-resistant options (\*)

Level 2 with anti-gripping and whole height fast and slow panels' boxing (Lock contact cowling included)

Vandal-resistant unlocking system

### Button boxes and cutouts

"CALL" button box (\*)

"CALL" round button(\*)

"CALL" Antivandal button box (\*)

Without button box

Without cutout

48 x 70 mm button box cutout

Special button box cutout : l \_\_\_\_\_ x H \_\_\_\_\_ (\*)

Indicator cutout on upright : l \_\_\_\_\_ x H \_\_\_\_\_ (\*)

axled at : \_\_\_\_\_ - With fireproof box (\*)

Additionnal upright cutout : l \_\_\_\_\_ x H \_\_\_\_\_ (\*)

axled at : \_\_\_\_\_ With fireproof box

Header indicator cutout - Maxi depth = 50 mm : l \_\_\_\_\_ x H \_\_\_\_\_ (\*) - Centered on CO

### Finishes (\*) ( primer finished standard)

304L brushed 220 massive stainless steel

Nb of doors : \_\_\_\_\_

304L leather texture D42 massive stainless steel

Nb of doors : \_\_\_\_\_

RAL powder coating \_\_\_\_\_

Nb of doors : \_\_\_\_\_

304L linen massive stainless steel

Nb of doors : \_\_\_\_\_

Other finishes : Contact us

Non fireproof glazing (\*)

On whole facade (4 glass) - Number of doors : \_\_\_\_\_

On panels only (3 glass) - Number of doors : \_\_\_\_\_

### Options

Standard aluminium sill

304 L non reinforced sill (\*)

304 L reinforced sill (\*)

Iron sill (\*)

Stainless steel toe guard (\*)

Cover plates (\*)  steel to paint

304L brushed st. steel

304L leather texture D42 st. steel

304L linen st. steel

Fixing dowels (\*)  protected steel  304L stainless steel

Unlocking key - Qty (\*) : \_\_\_\_\_

EN 81-21 safety contacts (\*)

1NO/1NF

2NF

24 V

230 V

On whole floors

On the lowest level door

Contacts cowling (\*)

Kit for unlocking the lowest landing door from the botton of pit (EN 81-20) (\*)

• Literature

French

English

German

Italian

### Miscellaneous

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_