

Company : .....  
 Order n° : .....  
 Lift n° : .....  
 Reference : .....  
 Technical contact : .....  
 Delivery address : .....

Delivery time requested

ORDER

QUOTATION

## 2 PANELS CENTRAL OPENING LANDING DOOR

**EN 81 - 20**  
 EN 81-58 : E 120 - EW 60  
**EN 81-71 Cat. 1**

**Rhea 2V OC**  
 CO 600 to 1100



**Small facade (HR) acc. drawing 2625900**

or

**Small facade (HR) «customized»**

**Uprights width**

- 110 (std)
- 150 (\*)
- 175 (\*)
- other (\*): \_\_\_\_\_ (mini : 110)

**Header height**

- 200 (std in sheet metal execution)
- 110 (\*)
- other (\*): \_\_\_\_\_ (mini : 110 maxi : 300)

**⚠ Header 110 mm not EN 81-20 and not compatible with car door locking device**

Qty : \_\_\_\_\_ CO : \_\_\_\_\_ CH : \_\_\_\_\_

**Full facade (FC) acc. drawing 2625700**

or

**Full facade (FC) «customized»**

**Uprights width**

- other (\*): \_\_\_\_\_ (mini : PL/2 + 50 - Maxi PL/2 + 75)

**Header height**

- 200 (std)
- other (\*): \_\_\_\_\_ (mini : 110 maxi : 300)

**Fixed in shaft acc. drawing 2626100**

- on swinging door frame
- behind a concrete bay

(☞ overhang in shaft : 90 mm)

Landing frame cladding is at the client's expense, or contact us

Overhang in shaft : \_\_\_\_\_ mm

- ☞ Protected iron squares for fixing in shaft (\*)
- ☞ 304 L stainless steel squares for fixing in shaft (\*)

### Vandal resistant options (\*)

- Category 1
- Reinforcement option (Panel's boxing + anti-gripping)
- Contact enclosure option

### Button boxes and cutouts

- Call push button (\*)
- Call + present push button
- Vandal resistant call push button
- Vandal resistant call + present push button
- 48 x 70 mm button box cutout
- Special button box cutout : l \_\_\_\_\_ x H \_\_\_\_\_ (\*) with fire-resistant box
- Without push button box
- Without cutout
- On upright :  Left  Right
- Indicator cutout on upright : l \_\_\_\_\_ x H \_\_\_\_\_ (\*)
- Additionnal upright cutout : l \_\_\_\_\_ x H \_\_\_\_\_ (\*) centered at : \_\_\_\_\_ With fire-resistant box
- Header indicator cutout - Maxi depth = 50 mm : l \_\_\_\_\_ x H \_\_\_\_\_ (\*) centered at : \_\_\_\_\_ - With fire-resistant box (\*)
- Centered on facade
- Centered on CO

### Finishes and glazing (\*)

- 304 Brushed massive stainless steel      ☞ Nb of doors : \_\_\_\_\_
- RAL powder coating \_\_\_\_\_      ☞ Nb of doors : \_\_\_\_\_
- 304 leather texture massive stainless steel      ☞ Nb of doors : \_\_\_\_\_
- 304 linen massive stainless steel      ☞ Nb of doors : \_\_\_\_\_

### Options

- Standard aluminium sill
- 304 L non reinforced sill (\*)
- 304 L reinforced sill (\*)
- Iron sill (\*)
- Stainless steel toe guard (\*)
- Cover strips (\*) ☞ steel to paint
- 304 brushed st. steel
- 304 leather texture D42 st. steel
- 304 linen st. steel
- Fixing dowels (\*) ☞ protected iron
- 304 stainless steel
- Emergency key release - Qty (\*) : \_\_\_\_\_
- EN 81-21 safety contacts (\*)
- Bistable  1NO/1NF
- 2NF
- 24 V
- 230 V
- Monostable
- Strengthening omegas in panels for CO < or = 800 mm (\*)
- Kit for unlocking the lowest landing door from the botton of pit (EN 81-20) (\*)

### Unlocking and driving (\*)

- Car door  replaced by a SLYCMA car door
- maintained
- ☞ brand : \_\_\_\_\_ model : \_\_\_\_\_ RC : \_\_\_\_\_
- Landing door(s) maintained
- ☞ brand : \_\_\_\_\_ model : \_\_\_\_\_ RC : \_\_\_\_\_ (in case of partial substitution)

- Literature  French  English  German  Italian

### Miscellaneous