

Company :
 Order n° :
 Lift n° :
 Reference :
 Technical contact :
 Delivery address :

Delivery time requested

ORDER

QUOTATION

2 PANELS SIDE OPENING LANDING DOOR

EN 81 - 20
 EN 81-58
 E 120 - EI 60

Rhea 2V OL

CO 600 to 1300

Sliding to the left side seen from landing



Qty : _____ CO : _____ CH : _____

Small facade (HR) acc. drawing 2625300

or

Small facade (HR) «customized»

Uprights width

- 110 (std)
- 150 (*)
- 175 (*)
- other (*): _____ (mini : 110)

Header height

- 200 (std in sheet metal execution)
- 215 (std in glazed execution)
- 145 (*)
- other (*): _____ (mini : 110 maxi : 300)

Overhang in shaft : _____ mm

☞ Cam for mechanical unlocking(*) - Nb of cams : _____
 (Door E120 with maxi overhang in shaft = 135 mm) - Caution car door JET-S

Antivandal options (*)

- Level 1 with fast panel's boxing on the whole height
- Lock contact cawling

Button boxes and cutouts

- "CALL" button box (*)
- "CALL" round button(*)
- "CALL" Antivandal button box (*)
- Indicator cutout on upright : l _____ x H _____ (*)
- Additionnal upright cutout : l _____ x H _____ (*)
 centered at : _____ - With fireproof box (*)
- Header indicator cutout - Maxi depth = 50 mm : l _____ x H _____ (*) -

Finishings and glazing (*)

- 304L brushed 220 massive stainless steel ☞ Nb of doors : _____
- RAL powder coating _____ ☞ Nb of doors : _____
- Panels' glazing **not fireproof** (acc. drawing 2651100) - Caution Maxi CO glazed = 1100 - Others contact us - Antivandal option not available for glazed executions
 - Panoramic : panels edges and sill aluminium anodized natural tone
 - Other finishes for panels edges and sill - Tone : _____
- 304L leathter texture D42 massive stainless steel ☞ Nb of doors : _____
- 304L linen massive stainless steel ☞ Nb of doors : _____
- Full Glass (Anodization and brightening following SLYCMA reference)

Options

- Standard aluminium sill
- 304 L non reinforced sill (*)
- 304 L reinforced sill (*)
- Iron sill (*)
- Stainless steel toe guard (*)
- Cover plates (*) ☞ steel to paint
- 304L brushed st. steel
- 304L leather texture D42 st. steel
- 304L linen st. steel
- Fixing dowels (*) ☞ protected steel
- 304L stainless steel
- Unlocking key - Qty (*) : _____
- Emergency release contact (*)
- EN 81-21 safety contacts (*)
- 1NO/1NF
- 2NF
- 24 V
- 230 V
- ☞ On whole floors
- On the lowest level door
- Kit for unlocking the lowest landing door from the botton of the pit (EN 81-20) (*)

Unlocking and driving (*)

Car door replaced by a SLYCMA car door
 maintained ☞ brand : _____ model : _____ RC : _____
 Landing door(s) maintained ☞ brand : _____ model : _____ RC : _____ (in case of partial substitution)

- Literature French English German Italian

Miscellaneous