



GAIA 2014/33/UE
EN 81-20/50

LANDING GLASS DOORS
FIRE-RESISTANT



GAIA

2 panels LANDING DOOR
Lateral and central opening
Fireproof glazed execution

Robust and easy to use are the main assets of this range.
Perfectly integrable in all the highly demanded environments such as office buildings, hotels, hospitals, shopping centers ... it can also be adapted to allow a complete or partial renovation.



GAIA landing door dimensions Lateral and central opening 2 panels (in mm)

	MINI	MAXI
Clear opening (CO)	600	1100
Clear Height (CH)	1900	2400
Standard header height	200	
Full facade	Bunch post width : CO/2 + 50 Slam post width : 110	
Small facade	Upright width : 110	

Pictures for illustration purpose only - SLYCMA production 2017


Certified fire-resistant
EN 30 accordint to EN 81-58

Ideal for **Création**
and **Modernization**



- Compliant with the EN 81 -20/50 standard
- Safety contacts available in accordance with the EN 81-21 standard
- Standard header 200 mm height


Finitions standard




Primer




220 brushed stainless steel (*)




Leather texture stainless steel (*)




Square st. steel (*)



Linen st. steel (*)



5WL st. steel (*)



RAL painting (*)

Glass



Clair (*)

*With extra cost

SLYCMA car door associated :
JET-S



SLYCMA Siège
Parc d'activité du Dôme
4 route du Dôme
69630 Chaponost
FRANCE
Tél. : +33 (0)4 78 86 81 00
Fax : +33 (0)4 78 86 81 08

SLYCMA Paris
34 route de Longjumeau
91380 Chilly-Mazarin
FRANCE
Tél. : +33 (0)1 69 79 32 10
Fax : +33 (0)1 69 79 32 15

www.slycma.com